

**IN THE CLAIMS**

Please amend the claims to read as indicated herein.

1. (currently amended) Supporting device for a portable device, comprising:

a supporting plate;

a supporting frame having (a) a first end that can be ~~mounted on a base~~ placed on a surface, and

(b) a second end adjustably arranged in a sliding guide located at said supporting plate; and

a lever, for elevating said supporting frame, having (a) a first end pivotally mounted at said supporting frame between said first end and said second end of said supporting frame,

around a first swivel axis running parallel to said ~~base~~ surface, and (b) a second end

pivotally mounted on said supporting plate below said sliding guide around a second swivel axis running parallel to said first swivel axis,

wherein said sliding guide has a locking recess along an edge bordering said supporting plate, and

wherein said second end of said supporting frame is movable along said sliding guide to vary a

distance between said second end of said supporting frame and said ~~first~~ second end of said lever, and engages said locking recess to support said portable device.

2. (previously presented) Supporting device according to claim 1, wherein said second end of said supporting frame is pivotally mounted around a third swivel axis that runs parallel to said first swivel axis and is adjustably arranged perpendicularly to said first swivel axis, along said supporting plate.

3. (currently amended) Supporting device according to claim 1,

wherein said supporting frame can be adjusted to a maximum position in which said supporting frame rests with a first side of said supporting frame on said ~~base~~ surface, and

wherein said supporting plate, with a supporting area above said sliding guide, rests on a second side of said supporting frame.

4. (currently amended) Supporting device according to claim 1, wherein said ~~first~~ second end of said lever is arranged closer to said second end of said supporting frame than to said first end of said supporting frame.

5. (previously presented) Supporting device according to claim 1,  
wherein said supporting frame can be adjusted to a "not in use" position in which said supporting frame rests with a first side of said supporting frame on a side of said supporting plate facing said supporting frame, and  
wherein said lever runs mostly parallel to said first side of said supporting frame and mostly parallel to said side of said supporting plate, between said supporting plate and said supporting frame.

6. (previously presented) Supporting device according to claim 5, wherein said supporting frame has a side with a recess into which said lever extends during said "not in use" position.

7. (previously presented) Supporting device according to claim 1, wherein said supporting plate has a side with a recess into which said supporting frame is arranged during said "not in use" position.

8. (previously presented) Supporting device according to claim 1,  
wherein said sliding guide is a first sliding guide and said lever is a first lever, and said supporting device further comprises a second sliding guide located at said supporting plate and a second lever,  
wherein said supporting frame is U-shaped with a first extension and a second extension,  
wherein said first lever is pivotally connected to said first extension, and said first extension is pivotally connected to said first sliding guide, and  
wherein said second lever is pivotally connected to said second extension, and said second extension is pivotally connected to said second sliding guide.

9. (previously presented) Supporting device according to claim 1, wherein said supporting device is an integral part of said portable device.

10. (previously presented) Supporting device according to claim 1, wherein said supporting device is a separate component of said portable device.

11. (previously presented) Supporting device according to claim 10, further comprising quick connectors to secure said supporting device to said portable device.

12. (previously presented) Supporting device according to claim 1, wherein said supporting device is impact resistant and/or impact absorbing.

13. (previously presented) Supporting device according to claim 1, wherein said supporting device is made of plastic.

14. (previously presented) Supporting device according to claim 1, wherein said portable device is for measuring or testing components of electrical circuits or optical networks.

15. (previously presented) Supporting device according to claim 1, wherein said portable device includes a time domain reflectometer (TDR).

16. (previously presented) Supporting device according to claim 1, wherein said portable device includes an optical time domain reflectometer (OTDR).

17. (previously presented) Supporting device according to claim 1, wherein said portable device is for testing a wavelength division multiplexing (WDM).

---